

Door Canopy

Door Canopies are attractive and efficient while eliminating the need and expense of drafting and manufacturing canopies as part of the building package.

Construction: 26 gauge material around an 18 gauge galvanized frame. Telescoping channels mount between girts on the interior of the building. Channels will accommodate girt spacing of up to 7' 6". 1/2" threaded rod connects channels to canopy frame. All hardware necessary for installation is included.

Finish: 26 gauge galvanized steel or aluminum. Unit can be painted after assembly to match most metal building colors to properly accent building trim.

Design: Incorporates a flat Soffit and an integral gutter drain. Canopy drains against building to the outside of the door jambs. Canopy can be installed in conjunction with any panel type or panel location. Units can be flashed together for continuous applications.

Standard Size: 4' 0" projection from face of wall, available in 4'6" width for single doors and 7' 6" width for double doors. Other sizes available upon request.

Loading: 4' 6" wide canopy rated for 55# PSF gravity loading and 49# PSF wind uplift = 114 M.P.H. if canopy is hung under 20' from ground. (Optional 100# PSF available upon request.) 7' 6" wide canopy rated for 55# PSF gravity loading and 38# PSF wind uplift = 100 M.P.H. if canopy is hung under 20' from ground. (Optional 100# PSF available upon request)

