

6070 Standard Preassembled Door

The Both Leafs Active (E Swing) Base Door package Includes the Following Components:

1. (2) 18 gauge, galvanized, insulated door leafs
2. 5 $\frac{3}{4}$ ", 16 galvanized, insulated, door frame; 6" extended face header for metal building, 4" face for 8" block walls and 2" face for metal/wood stud walls
3. 16 gauge, galvanized subframe (framed opening) sized to match girt depth for metal buildings or existing opening anchors for metal stud, concrete/block, or wood walls; wire anchors also available for block walls
4. Removable mullion
5. (2) standard duty rim panics w/ standard levers (689 finish)
6. (2) standard duty door closers w/ standard parallel arms (689 finish)
7. (6) ball-bearing hinges – 4 $\frac{1}{2}$ " x 4 $\frac{1}{2}$ " with a non-removable pin (689 finish)
8. 5 $\frac{3}{4}$ ", aluminum threshold
9. (2) sweeps
10. Adjustable, full aluminum channel weatherseal
11. 12 gauge, galvanized, adjustable mounting clips
12. All fasteners and anchors included for complete installation
13. *Optional Fire Rated* doors include a 90 minute or 3 hour rating and a standard duty closer with parallel arm
14. *Optional Wind Rated* doors include 2 heavy duty panics and a wind rated mullion

