

# WINTTECH

## 225 Series Aluminum Hung



CPD #	U-factor	SHGC	VT	Condensation Resistance	Low-E	Gap Widths	Spacer	Overall Glass Thickness	GapFill	Label Number
WNT-A-6-00001-00001	0.64	0.69	0.7	18	# 2	0.438	Polycarb	7/16	AIR (100%)	547
WNT-A-6-00002-00001	0.49	0.24	0.41	18	# 3	0.438	Polycarb	7/16	AIR (100%)	548
WNT-A-6-00003-00001	0.49	0.36	0.41	18	# 2	0.438	Polycarb	7/16	AIR (100%)	
WNT-A-6-00004-00001	0.5	0.26	0.47	18	# 2 & # 3	0.438	Polycarb	3/8	AIR (100%)	
WNT-A-6-00005-00001	0.48	0.21	0.24	18	# 3	0.438	Polycarb	3/8	AIR (100%)	
WNT-A-6-00006-00001	0.65	0.55	0.52	18	# 3	0.438	Polycarb	3/8	AIR (100%)	
WNT-A-6-00007-00001	0.5	0.36	0.47	18	# 2	0.438	Polycarb	3/8	AIR (100%)	
WNT-A-6-00008-00001	0.5	0.24	0.34	18	# 2 & # 3	0.438	Polycarb	7/16	AIR (100%)	
WNT-A-6-00009-00001	0.49	0.21	0.17	18	# 2 & # 3	0.438	Polycarb	7/16	AIR (100%)	
WNT-A-6-00010-00001	0.65	0.68	0.7	18	# 3	0.375	Polycarb	3/8	AIR (100%)	
WNT-A-6-00011-00001	0.65	0.53	0.48	18	# 3	0.375	Polycarb	3/8	AIR (100%)	
WNT-A-6-00012-00001	0.5	0.28	0.32	18	# 3	0.375	Polycarb	3/8	AIR (100%)	

547

**WinTech Window Technology, Inc.**  
225 Aluminum Frame  
Double Glazing - Air Fill  
Product Type: Vertical Slider  
CPD# WNT-A-6-00001-00001

**CERTIFIED**

ENERGY PERFORMANCE RATINGS	
U-Factor (U.S.,I-P)	Solar Heat Gain Coefficient
<b>.64</b>	<b>.69</b>

**ADDITIONAL PERFORMANCE RATINGS**  
Visible Transmittance **.70**

Manufacture certifies that these ratings conform to applicable NFRC procedures for determining whole product energy performance. NFRC ratings are determined for a broad set of environmental conditions and specific product use. NFRC does not rate or certify products that do not meet the stability or any other applicable NFRC requirements. Consult manufacturer literature for other performance information.

Glazing - 5" - SSB x Air x SSB Clear  
Glazing complies with ASTM E 1300.  
Glazing complies with ASTM E 330-10 as tested.  
Windload Structural Performance Tested: 50 PSF  
Tested in accordance to ANNA/WDMA/CSA 1011.5, 2/0440-06 and ANNA/WDMA/CSA 1011.5, 2/0440-08

548

**WinTech Window Technology, Inc.**  
225 Aluminum Frame  
Double Glazing - Air Fill - Low E  
Product Type: Vertical Slider  
CPD# WNT-A-6-00002-00001

**CERTIFIED**

ENERGY PERFORMANCE RATINGS	
U-Factor (U.S.,I-P)	Solar Heat Gain Coefficient
<b>.49</b>	<b>.24</b>

**ADDITIONAL PERFORMANCE RATINGS**  
Visible Transmittance **.41**

Manufacture certifies that these ratings conform to applicable NFRC procedures for determining whole product energy performance. NFRC ratings are determined for a broad set of environmental conditions and specific product use. NFRC does not rate or certify products that do not meet the stability or any other applicable NFRC requirements. Consult manufacturer literature for other performance information.

Glazing - 5/8" - SSB Low E (F2) x Air x SSB Clear  
Glazing complies with ASTM E 1300.  
Glazing complies with ASTM E 330-10 as tested.  
Windload Structural Performance Tested: 50 PSF  
Tested in accordance to ANNA/WDMA/CSA 1011.5, 2/0440-06 and ANNA/WDMA/CSA 1011.5, 2/0440-08

225 Series Slider