

# WINTECH



## 225 Series Aluminum Hung

CPD #	Glass Make-Up	U-factor	SHGC	VT	CRF	Low-E Surface	Gap Widths	Spacer	Overall Glass Thickness	GapFill	Label Number
WNT-A-6-00001-00001	5/8" SSB Clear IG*	0.64	0.69	0.70	18	No Low-e	0.438	DuraSeal	5/8"	AIR (100%)	547
WNT-A-6-00002-00001	5/8" SSB Low E/Cir IG**	0.49	0.24	0.41	18	# 3	0.438	DuraSeal	5/8"	AIR (100%)	548
WNT-A-6-00003-00001	5/8" SSB Clr/Low E IG	0.49	0.26	0.41	18	# 2	0.438	DuraSeal	5/8"	AIR (100%)	
WNT-A-6-00004-00001	5/8" SSB Low E/Cir IG W/Argon	0.50	0.36	0.47	18	# 2	0.438	DuraSeal	5/8"	90% Argon	
WNT-A-6-00005-00001	5/8" SSB Clr/Low E IG W/Argon	0.48	0.21	0.24	18	# 3	0.438	DuraSeal	5/8"	90% Argon	
WNT-A-6-00010-00001	5/8" DSB Clear IG	0.65	0.68	0.70	18	No Low-e	0.375	DuraSeal	5/8"	AIR (100%)	
WNT-A-6-00011-00001	5/8" DSB Tint E/Cir IG**	0.65	0.53	0.48	18	# 2	0.375	DuraSeal	5/8"	AIR (100%)	
WNT-A-6-00012-00001	5/8" DSB Clr/Tint IG	0.50	0.28	0.32	18	# 3	0.375	DuraSeal	5/8"	AIR (100%)	

## 225 Series Aluminum Slider

WNT-A-5-00001-00001	5/8" SSB Clear IG*	0.65	0.69	0.71	18	No Low-e	0.438	DuraSeal	5/8"	AIR (100%)	545
WNT-A-5-00002-00001	5/8" SSB Low E/Cir IG**	0.50	0.24	0.41	18	# 2	0.438	DuraSeal	5/8"	AIR (100%)	546
WNT-A-5-00003-00001	5/8" SSB Clr/Low E IG	0.5	0.36	0.41	18	# 3	0.438	DuraSeal	5/8"	AIR (100%)	
WNT-A-5-00004-00001	5/8" SSB Low E/Cir IG W/Argon	0.51	0.26	0.47	18	# 2	0.438	DuraSeal	5/8"	90% Argon	
WNT-A-5-00005-00001	5/8" SSB Clr/Low E IG W/Argon	0.49	0.21	0.24	18	# 3	0.438	DuraSeal	5/8"	90% Argon	
WNT-A-5-00010-00001	5/8" DSB Clear IG	0.66	0.68	0.7	18	No Low-e	0.375	DuraSeal	5/8"	AIR (100%)	
WNT-A-5-00011-00001	5/8" DSB Tint E/Cir IG**	0.66	0.53	0.48	18	# 2	0.375	DuraSeal	5/8"	AIR (100%)	
WNT-A-5-00012-00001	5/8" DSB Clr/Tint IG	0.51	0.28	0.32	18	# 3	0.375	DuraSeal	5/8"	AIR (100%)	

### Horizontal Slider Sticker

545\*

225 Aluminum Frame  
Double Glazing - Air Fill - Low E  
Product Type: Horizontal Slider  
CPD# WNT-A-5-00010-00001

**CERTIFIED**  
National Fenestration Rating Council

**ENERGY PERFORMANCE RATINGS**  
U-Factor (U.S.I.P.) Solar Heat Gain Coefficient

**ADDITIONAL PERFORMANCE RATINGS**  
Visible Transmittance

0.65  
0.69  
0.71

0.24  
0.26  
0.28

0.41  
0.47  
0.50

18  
18  
18

5/8" SSB Clear IG  
5/8" SSB Low E/Cir IG\*\*  
5/8" SSB Clr/Low E IG  
5/8" SSB Low E/Cir IG W/Argon  
5/8" SSB Clr/Low E IG W/Argon

5/8" DSB Clear IG  
5/8" DSB Tint E/Cir IG\*\*  
5/8" DSB Clr/Tint IG

545

WinTech Window Technology, Inc.  
225 Aluminum Frame  
Double Glazing - Air Fill - Low E  
Product Type: Horizontal Slider  
CPD# WNT-A-5-00010-00001

**CERTIFIED**  
National Fenestration Rating Council

**ENERGY PERFORMANCE RATINGS**  
U-Factor (U.S.I.P.) Solar Heat Gain Coefficient

**ADDITIONAL PERFORMANCE RATINGS**  
Visible Transmittance

0.65  
0.69  
0.71

0.24  
0.26  
0.28

0.41  
0.47  
0.50

18  
18  
18

5/8" SSB Clear IG  
5/8" SSB Low E/Cir IG\*\*  
5/8" SSB Clr/Low E IG  
5/8" SSB Low E/Cir IG W/Argon  
5/8" SSB Clr/Low E IG W/Argon

5/8" DSB Clear IG  
5/8" DSB Tint E/Cir IG\*\*  
5/8" DSB Clr/Tint IG

545

546\*\*

225 Aluminum Frame  
Double Glazing - Air Fill - Low E  
Product Type: Horizontal Slider  
CPD# WNT-A-5-00010-00001

**CERTIFIED**  
National Fenestration Rating Council

**ENERGY PERFORMANCE RATINGS**  
U-Factor (U.S.I.P.) Solar Heat Gain Coefficient

**ADDITIONAL PERFORMANCE RATINGS**  
Visible Transmittance

0.50  
0.24  
0.41

0.69  
0.70  
0.71

0.28  
0.32  
0.32

0.48  
0.48  
0.48

18  
18  
18

5/8" SSB Clear IG  
5/8" SSB Low E/Cir IG\*\*  
5/8" SSB Clr/Low E IG  
5/8" SSB Low E/Cir IG W/Argon  
5/8" SSB Clr/Low E IG W/Argon

5/8" DSB Clear IG  
5/8" DSB Tint E/Cir IG\*\*  
5/8" DSB Clr/Tint IG

546\*\*

547\*

225 Aluminum Frame  
Double Glazing - Air Fill  
Product Type: Vertical Slider  
CPD# WNT-A-5-00010-00001

**CERTIFIED**  
National Fenestration Rating Council

**ENERGY PERFORMANCE RATINGS**  
U-Factor (U.S.I.P.) Solar Heat Gain Coefficient

**ADDITIONAL PERFORMANCE RATINGS**  
Visible Transmittance

0.64  
0.69  
0.70

0.26  
0.28  
0.32

0.47  
0.48  
0.48

18  
18  
18

5/8" SSB Clear IG  
5/8" SSB Low E/Cir IG\*\*  
5/8" SSB Clr/Low E IG  
5/8" SSB Low E/Cir IG W/Argon  
5/8" SSB Clr/Low E IG W/Argon

5/8" DSB Clear IG  
5/8" DSB Tint E/Cir IG\*\*  
5/8" DSB Clr/Tint IG

547\*

548\*\*

225 Aluminum Frame  
Double Glazing - Air Fill - Low E  
Product Type: Vertical Slider  
CPD# WNT-A-5-00010-00001

**CERTIFIED**  
National Fenestration Rating Council

**ENERGY PERFORMANCE RATINGS**  
U-Factor (U.S.I.P.) Solar Heat Gain Coefficient

**ADDITIONAL PERFORMANCE RATINGS**  
Visible Transmittance

0.49  
0.24  
0.41

0.69  
0.70  
0.71

0.28  
0.32  
0.32

0.48  
0.48  
0.48

18  
18  
18

5/8" SSB Clear IG  
5/8" SSB Low E/Cir IG\*\*  
5/8" SSB Clr/Low E IG  
5/8" SSB Low E/Cir IG W/Argon  
5/8" SSB Clr/Low E IG W/Argon

5/8" DSB Clear IG  
5/8" DSB Tint E/Cir IG\*\*  
5/8" DSB Clr/Tint IG

548\*\*